

Bron Square Fixed Trimless




DOWNLIGHT | Product code MD41

MONDOLUX™
mondolux.com.au



Cutting-edge adaptability

- Included as part of the Infinito Series
- Modular design with the flexibility to adapt the fitting based on requirements
- High efficiencies for deep baffle option
- Wattage options: 7W, 13W, 18W



Bron Square Fixed Trimless

DOWNLIGHT | Product code MD41

Product info

System Lumen Range	675lm — 1830lm
System Power	7W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Body/Trim Colour	White, Black
Installation Method	Fixed Recessed, Trimless Fixed Recessed
LED Brand	CREE, Bridgelux
Dimming Type	Phase-Cut Dimmable, Wireless Dimmable (Casambi), Non-Dimmable, DALI Dimmable
Accessories	Black Baffle, Chrome Baffle, Rose Gold Baffle, White Baffle, Deep Baffle + Black Baffle, Deep Baffle + Chrome Baffle, Deep Baffle + Rose Gold Baffle, Deep Baffle + White Baffle, Deep Baffle + Black Baffle + D, Deep Baffle + Black Baffle + F, Deep Baffle + Black Baffle + H, Deep Baffle + Black Baffle + I, Deep Baffle + Black Baffle + L, Deep Baffle + Chrome Baffle +, Deep Baffle + White Baffle + D, Deep Baffle + White Baffle + F, Deep Baffle + White Baffle + H, Deep Baffle + White Baffle + I, Deep Baffle + White Baffle + L, Black Baffle + Diamond Diffuse, Black Baffle + Frosted Diffuse, Black Baffle + Honeycomb Louvr, Black Baffle + IP44 Diffuser, Black Baffle + Line Diffuser, Chrome Baffle + Diamond Diffus, Chrome Baffle + Frosted Diffus, Chrome Baffle + Honeycomb Louv, Chrome Baffle + IP44 Diffuser, Chrome Baffle + Line Diffuser, Rose Gold Baffle + Diamond Dif, Rose Gold Baffle + Frosted Dif, Rose Gold Baffle + Honeycomb L, Rose Gold Baffle + IP44 Diffus, Rose Gold Baffle + Line Diffus, White Baffle + Diamond Diffuse, White Baffle + Frosted Diffuse, White Baffle + Honeycomb Louvr, White Baffle + IP44 Diffuser, White Baffle + Line Diffuser

Bron Square Fixed Trimless

DOWNLIGHT | Product code MD41

Photometric info

Colour Rendering Index (CRI)	CRI90, CRI97+
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

Compliance and Features



Packaging

Box Dimensions L x W x H mm	110 mm x 110 mm x 200 mm
Boxes per Carton	24
Carton Weight	12 KG
Carton Dimensions L x W x H mm	450 mm x 340 mm x 410 mm

Polar distribution diagrams

