

Linea COB LED Strip

Consistent, even illumination

- Seamless LED Strip for uniform lighting
- 24V DC
- >CRI90
- 85lm/w
- New integrated LED packaging technology delivers high intensity, uniform light without any hot spots

ENQUIRE NOW

NEW



Linea COB LED Strip

mondolux.com.au




Introducing Linea COB LED Strip, the new linear strip that offers consistent, even illumination. The new LED packaging technology delivers a high intensity, uniform and compact solution for extrusions with any depth. As the LED Strip has no visible individual LED's, it's also a great solution for joinery applications with gloss and reflective surfaces.



Available Options:

- Lumen Output: 1029lm, 1527lm
- System Power: 10W/m, 16W/m
- Beam Angle: 140°
- Input Voltage: 24V Constant Voltage
- Cuttable Length: 50mm
- IP43 Rated
- Dimming Type: Non-Dimmable, DALI Dimmable
- Colour Temperature (CCT): 2700K, 3000K, 4000K
- Colour Rendering Index (CRI): CRI90



Code Information

| Family Code + | Product + | Installation Type + | PCB Width + | Chip Model + | CRI + | CCT + | LEDs/m + | Voltage + | IP + |
|----------------------|--------------------|----------------------|-------------|--------------|-----------|------------|-----------|-----------|-------------|
| ML = Mondolux Linear | 15 = Linea COB 10W | SM = Surface Mounted | 4 = 10mm | D = COB | 9 = CRI90 | 27 = 2700K | 480 = 480 | 24V = 24V | IP43 = IP43 |
| | 16 = Linea COB 16W | | | | | 30 = 3000K | | | |
| | | | | | | 40 = 4000K | | | |

Example: ML15SM40-930-480-24V-IP43

Mondolux Flexible Strip Linea COB Surface Mounted 10W 24VDC 10mm Width IP43 CRI90 3000K 1029lm 480leds 50mm Cuttable Length

Example: MD16SM40-940-480-24V-IP43

Mondolux Flexible Strip Linea COB Surface Mounted 16W 24VDC 10mm Width IP43 CRI90 3000K 1527lm 480leds 50mm Cuttable Length