





Lights, Camera, Modena!

- Also available in Maxi size
- Efficacy of 95lm/W at CRI90
- Tilting angle range of 0°-90° and rotation angle up to 350°
- Features enhanced lighting capabilities with honeycomb louvre and barn door accessories

Product info

System Lumen Range	1250lm — 2650lm
System Power	20W, 28W
Forward Current	500mA, 700mA
System Efficacy Range	63lm/W to 95lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	3-Circuit Track Mounted, Surface Mounted, 1-Circuit Track Mounted
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable
Maximum Tilt Angle	90°
Maximum Rotation Angle	350°, 0
Accessories	Without Accessory, Honeycomb Louvre, Barn Doors, Barn Door
Warranty	5 years (T&C apply)
Custom Dimming Type	Available on request



Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid
Beam Angle	14°, 20°, 40°
Light Output Ratio (LOR)	100
Unified Glare Rating (UGR)	<UGR17
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

Compliance

RoHS




Packaging


Box Weight	1.15kg
Box Dimensions L x W x H mm	130 mm x 130 mm x 310 mm
Boxes per Carton	15
Carton Dimensions L x W x H mm	670 mm x 405 mm x 325 mm

Polar distribution diagrams

Modena Mini 14°



Modena Mini 21°



Modena Mini 43°

