


## Redefining intelligence and excellence




- Highly energy efficient with efficacy of 160lm/W at CRI80
- Pre-wired trunking rail for connection: 5,7,11 wires
- Multiple beam angle options of 25°, 30°, 60°, 90°, Single Asymmetric, Double Asymmetric
- Amazing add-on features: Emergency/Sensor/Dimming/Track light modules
- Reduced usage, installation and maintenance costs
- Length options: 567mm, 1410mm that can be used to run desirable lengths of uniform lighting

### Product info

System Lumen Range	2560lm — 12800lm
System Power	16W, 20W, 26W, 32W, 40W, 50W, 65W, 80W
Forward Current	400mA, 500mA, 650mA, 800mA, 1000mA, 1300mA, 1650mA, 2000mA
System Efficacy Range	160lm/W to 160lm/W
Body/Trim Colour	White
Installation Method	Surface Mounted / Suspended
LED Brand	Hongli
Dimming Type	Non-Dimmable
Accessories	Without Accessory
Length	567mm, 1410mm
Custom Dimming Type	Available on Request



Note: Drawing not to scale



Note: Drawing not to scale

### Photometric info

Colour Rendering Index (CRI)	CRI80
Colour Temperature (CCT)	4000K
Beam Angle	25°, 30°, 60°, 90°
Custom Colour Temperature (CCT)	Available on Request

## Compliance

---



RoHS