




Modular LED Floodlighting

The Nilum LED Floodlight series is a modular system of industrial quality outdoor lighting which provides a variety of wattage and optical options within a common housing style.

- Protective UV stabilised powder coated finish
- Applications: Industrial lighting, building facades, area lighting, general floodlighting
- Optic Options: 20°x20° / 30°x30° / 60°x60° / 50°x140° / 30°x100° / 40°x100° / 30°x140° / 140°x140°

Product info

System Lumen Range	26000lm — 35000lm
System Power	160W, 220W
System Efficacy Range	159lm/W to 163lm/W
Input Voltage	240V
Body/Trim Colour	Black
Installation Method	Surface Mounted
LED Brand	Lumileds
IP Rating	IP65
Dimming Type	0-10V Dimmable, Non-Dimmable
Accessories	Without Accessory



Photometric info

Colour Rendering Index (CRI)	CRI70
Colour Temperature (CCT)	4000K
Beam Angle	20°, 30°, 40°, 50°, 60°, 140°
Custom Colour Temperature (CCT)	Available on request
Custom Colour Rendering Index (CRI)	Available on request

Nilum Plus II

FLOOD
LIGHT

Product code MF22

mondolux.com.au

MONDOLUX™

Packaging

Boxes per Carton	0, 1
------------------	------
