


Wall lighting, now sorted



- Innovative wall-washing solution providing a smooth distribution of light from ceiling to floor
- Higher spatial flexibility with vertical tilt up to 60°
- Available in 13W, 19W, 28W, 36W, 43W
- Asymmetric beam angle of 90°x75°
- Padua 900mA approved under VEU and IPART

Product info

System Lumen Range	850lm — 3200lm
System Power	13W, 19W, 28W, 36W, 43W
Forward Current	350mA, 500mA, 700mA, 900mA, 1050mA
System Efficacy Range	65lm/W to 74lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable
Maximum Tilt Angle	60°
VEU/IPART Approved	Padua 900mA (2900lm)/
Accessories	Without Accessory
Custom Dimming Type	Available on request



Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 4000K
Beam Angle	90°x75°
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

Compliance and Features

RoHS

CE



Packaging

Box Weight	1 kg
Box Dimensions L x W x H mm	250 mm x 180 mm x 130 mm
Boxes per Carton	12
Carton Dimensions L x W x H mm	540 mm x 500 mm x 260 mm

Polar distribution diagrams

