


Solid modesty



- Phase Cut and DALI Dimmability options are available
- Flexible mounting clip to accommodate ceiling thicknesses ranging from 5mm to 30mm
- Trim Ø160mm, cut-out Ø150mm, 13W - 50W
- 30° maximum tilt angle

Product info

System Lumen Range	950lm — 4400lm
System Power	13W, 20W, 27W, 36W, 43W, 50W
Forward Current	350mA, 500mA, 700mA, 900mA, 1050mA, 1200mA
System Efficacy Range	73lm/W to 88lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable, Phase-Cut Dimmable
Maximum Tilt Angle	30°
Maximum Rotation Angle	355°
Accessories	Without Accessory
Custom Dimming Type	Available on request



Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid
Beam Angle	10°, 18°, 28°, 48°
Light Output Ratio (LOR)	>87%
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

Compliance

RoHS




Packaging


Box Weight	1kg
Box Dimensions L x W x H mm	180 mm x 180 mm x 155 mm
Boxes per Carton	12
Carton Dimensions L x W x H mm	370 mm x 370 mm x 470 mm

Polar distribution diagrams

Polar 18°



Polar 29°



Polar 48°

