Queens Adjustable

DOWNLIGHT | Product code MD55

mondolux.com.au

MONDOLUX™

Intelligent elegance

- Comes in both fixed and adjustable options
- High CRI at 90
- Multiple beam angles covering all the beamspreads
- Dimmability option: Phase Cut

Product info

System Lumen Range	680lm — 2100lm
System Power	13W, 19W, 28W
Forward Current	350mA, 500mA, 700mA
System Efficacy Range	52lm/W to 75lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable, Phase-Cut Dimmable
Maximum Tilt Angle	30°
Maximum Rotation Angle	360°
Accessories	Without Accessory
Custom Dimming Type	Available on request

Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid
Beam Angle	20°, 25°, 36°, 65°
Light Output Ratio (LOR)	100
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

Queens Adjustable

DOWNLIGHT | Product code MD55

mondolux.com.au

MONDOLUX™

Compliance

CE RoHS

Packaging

Box Weight	0.6kg
Box Dimensions L x W x H mm	180 mm x 140 mm x 140 mm
Boxes per Carton	27
Carton Dimensions L x W x H mm	570 mm x 440 mm x 440 mm

Polar distribution diagrams

Queens 20°

Queens 25°

Queens 36°

Queens 65°