




Intelligent elegance

- Comes in both fixed and adjustable options
- High CRI at 90
- Multiple beam angles covering all the beamspreads

Product info

System Lumen Range	680lm — 3900lm
System Power	13W, 19W, 28W, 32W
Forward Current	350mA, 500mA, 700mA, 900mA
System Efficacy Range	52lm/W to 122lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable, Phase-Cut Dimmable
Maximum Tilt Angle	30°
Maximum Rotation Angle	360°
Accessories	Without Accessory
Warranty	5 years (T&C apply)



db
Ø100mm

Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid
Beam Angle	20°, 25°, 36°, 60°, 65°
Light Output Ratio (LOR)	>80%
Revit Files	Please choose Beam Angle / Power within the Revit file

Queens Adjustable

DOWNLIGHT

Product code MD55

mondolux.com.au

MONDOLUX™

Compliance and Features




RoHS

Packaging


Box Weight	0.6kg
Box Dimensions L x W x H mm	180 mm x 140 mm x 140 mm
Boxes per Carton	27
Carton Dimensions L x W x H mm	570 mm x 440 mm x 440 mm

Polar distribution diagrams


Queens 20°



Queens 25°



Queens 36°



Queens 65°

