


## Classic and compact



- Also comes in Ø90mm cut-out version
- System lumen range from 750lm - 950lm
- IP rated at IP40
- Compact body with efficient optics

## Product info

System Lumen Range	750lm — 950lm
System Power	9.5W, 13.5W
Forward Current	350mA, 500mA
System Efficacy Range	70lm/W to 79lm/W
Body/Trim Colour	White, Black
Installation Method	Fixed Recessed
IP Rating	IP40
Dimming Type	Phase-Cut Dimmable, Non-Dimmable, DALI Dimmable
Accessories	Without Accessory
Custom Dimming Type	Available on request



## Photometric info

Colour Rendering Index (CRI)	CRI80
Colour Temperature (CCT)	2700K, 3000K, 4000K
Beam Angle	24°, 35°, 60°
Light Output Ratio (LOR)	>83%
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

# Stirling 70

DOWNLIGHT

Product code MD05

mondolux.com.au

**MONDO LUX™**

## Compliance



**RoHS**

## Packaging

Box Dimensions L x W x H mm	115 mm x 115 mm x 115 mm
-----------------------------	--------------------------

Boxes per Carton	20, 0
------------------	-------

Carton Dimensions L x W x H mm	600 mm x 570 mm x 250 mm
--------------------------------	--------------------------

## Polar distribution diagrams

