

T-Bar Lumo 595mm x 595mm x 10mm

PANEL

Product code MP02

mondolux.com.au

MONDOLUX™




The ultimate efficiency upgrade

- Available in four different cut-outs: 1195mm x 595mm, 595mm x 595mm, 595mm x 295mm, 1195mm x 295mm
- Symmetric beam spread with a beam angle of 110°
- UV stable PMMA light guiding plate prevents discolouring over time
- Highly efficient 100lm/W

Product info

System Lumen Range	3400lm — 5000lm
System Power	32W, 40W, 54W
Forward Current	750mA, 760mA, 980mA, 1000mA, 1280mA, 1300mA
System Efficacy Range	93lm/W to 106lm/W
Input Voltage	240V
Body/Trim Colour	White
Installation Method	Fixed Recessed
IP Rating	IP40
Diffuser	Opal
Dimming Type	Non-Dimmable, DALI Dimmable
Accessories	Without Accessory
Warranty	3 years (T&C apply)
Custom Dimming Type	Available on request



Photometric info

Colour Rendering Index (CRI)	CRI80
Colour Temperature (CCT)	4000K
Beam Angle	110°
Light Output Ratio (LOR)	>90%
Custom Colour Temperature (CCT)	Available on request

Compliance

RoHS



T-Bar Lumo 595mm x 595mm x 10mm

PANEL | Product code MP02

mondolux.com.au



Packaging

Box Weight	3.5kg
Box Dimensions L x W x H mm	655 mm x 33 mm x 705 mm
Boxes per Carton	6, 0
Carton Dimensions L x W x H mm	655 mm x 200 mm x 705 mm