





Unconventionally clever

- Mounting options include track and surface mount
- Phase-cut dimmable option available
- High LOR of >88%

Product info

| | |
|------------------------|--|
| System Lumen Range | 1200lm — 2400lm |
| System Power | 20W, 28W |
| Forward Current | 500mA, 700mA |
| System Efficacy Range | 60lm/W to 86lm/W |
| Input Voltage | 240V |
| Body/Trim Colour | White, Black |
| Installation Method | 3-Circuit Track Mounted, Surface Mounted |
| LED Brand | Citizen |
| IP Rating | IP20 |
| Diffuser | Clear |
| Dimming Type | Non-Dimmable, Phase-Cut Dimmable |
| Maximum Tilt Angle | 90° |
| Maximum Rotation Angle | 355° |
| Accessories | Without Accessory, Honeycomb Louvre |
| Warranty | 5 years (T&C apply) |
| Custom Dimming Type | Available on request |



Photometric info

| | |
|---------------------------------|--|
| Colour Rendering Index (CRI) | CRI90 |
| Colour Temperature (CCT) | 3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid |
| Beam Angle | 14°, 20°, 45° |
| Light Output Ratio (LOR) | 100 |
| Custom Colour Temperature (CCT) | Available on request |
| Revit Files | Please choose Beam Angle / Power within the Revit file |

Compliance

RoHS



Packaging

| | |
|--------------------------------|--------------------------|
| Box Weight | 1.55kg |
| Box Dimensions L x W x H mm | 165 mm x 130 mm x 200 mm |
| Boxes per Carton | 16 |
| Carton Dimensions L x W x H mm | 545 mm x 355 mm x 430 mm |

Polar distribution diagrams

